

**DESCRIPTION:**

- Surewall Textured Coating is a high-quality, exterior/interior, 100% acrylic polymer-based protective and decorative textured coating.
- It exhibits excellent hiding power, mildew and alkali resistance, flexibility, and drying characteristics.

USES:

Surewall Textured Coating is used as:

- An exterior protective and decorative coating over surfaces of concrete, masonry, stucco, wood, metal, or acrylic-based textured coatings. It is compatible with Surewall finishes and may be applied over them.
- An interior protective and decorative coating over prepared drywall, concrete, or masonry surfaces.

COMPOSITION:

- Binder base: 100% acrylic polymers
- Color: White or tinted to desired color.
- Pigment base: Titanium dioxide

PROPERTIES:

- Adhesion: Excellent adhesion to compatible, properly prepared surfaces.
- Appearance: Flat non-gloss sanded texture.
- Washability: Can be washed with mild detergent solutions.
- Vapor permeability: Water vapor-permeable. Does not create a vapor barrier.

Textured Coating

COVERAGE:

Approximately 500–700 ft.² (45–63m²) per pail, per coat, depending upon the method of application and surface to which it is applied.

CONTAINER:

- 60-lb (27.2 kg) net weight in plastic pails
- Storage: Protect from sun and freezing at all times.
- Shelf life: One year if protected from sun and freezing.

DRYING TIME:

Approximately 1–4 hours depending on temperature, humidity, and substrate. Can be recoated after eight hours. Allow minimum five days curing before scrubbing surface.

CLEAN-UP:

Water soluble prior to drying. Clean tools and containers with water prior to drying.

SURFACE PREPARATION

- Remove surface contaminants such as dust or dirt without damaging the substrate. For previously painted surfaces, all loose and chalking paint must be removed, and glossy surfaces must be dulled.
- New concrete and masonry must be clean and cured a minimum of 28 days. Concrete surfaces shall be checked for alkalinity and treated. Any form release agent or bond breaker must be removed.
- Uneven concrete or masonry can be leveled with Surewall Flex Base or other suitable, compatible products.
- Gypsum wall board (interior application only): Treat as with normal drywall finishing and priming procedures.
- Metal surfaces: Chemically or physically remove oxides from surface and prime with two coats of non-oil-based metal primer.
- For additional options, contact Technical Services.

MIXING:

- Stir Surewall Textured Coating to a uniform consistency.
- Avoid creating air bubbles or foam.
- Stir occasionally as needed to keep uniformly mixed.

APPLICATION:

- Surewall Textured Coating exhibits good surface coverage in single applications. However, for most uncoated, unprimed surfaces of concrete, masonry, or drywall, to achieve adequate hiding of the substrate, one coat of Pre-Coat Acrylic Primer should be applied before applying Surewall Textured Coating.
- A diluted coat of Surewall Textured Coating may also be used as a primer. To use Surewall Textured Coating as the primer, add a small amount of clean, potable water: maximum 16 oz. (.48L) per pail.
- Surewall Textured Coating is easily applied with a roller or suitable spray equipment. A 3/16" (4.7mm) nap roller should be used to achieve a consistent texture. Apply Surewall Textured Coating as packaged. If necessary, add a small amount of clean, potable water: maximum 8 oz. (1 cup/.24L) per pail. Avoid an excessive build-up of Surewall Textured Coating when "cutting-in" with a brush around borders. Excessive build-up can result in unsightly appearance irregularities on the wall. Thinning Surewall Textured Coating some with water when using it to cut-in, and brushing out the Surewall Textured Coating, help to avoid excessive build-up.

LIMITATIONS:

- Ambient and surface temperature must be 40°F (4°C) or higher during application and drying time. Supplemental heat and protection from precipitation must be provided as needed.
- Use only on surfaces that are sound, clean, dry, and free from any residue that might affect the ability of Surewall Textured Coating to bond to the surface.

Job name _____

Contractor _____

Date _____

Submittal Approvals:
(Stamps or Signatures)

RES Architectural Sales, Inc.